

Technical Data

Product: Central Vacuum Supply System CVS 500 – incl. 2 x SOGEVAC SV 200
Part No.: 504312V053

Volume vacuum vessel:	500 l
Installed vacuum pump:	2 x SOGEVAC SV 200
Inlet connection vacuum vessel:	G 2", Inside thread
Outlet connection:	G 2", Inside thread
Nominal pumping speed at 50 Hz:	360 m ³ /h
Nominal pumping speed at 60 Hz:	440 m ³ /h
Pumping speed at 50 Hz:	340 m ³ /h
Pumping speed at 60 Hz:	400 m ³ /h
Ultimate total pressure without gas ballast:	≤ 0,08 mbar
Ultimate total pressure with gas ballast:	≤ 0,7 mbar
Water vapor tolerance at 50 Hz:	40 mbar
Water vapor tolerance at 60 Hz:	50 mbar
Water vapor capacity at 50 Hz:	6800 g/h
Water vapor capacity at 60 Hz:	10800 g/h
Operating fluid:	LVO 130
Operating fluid capacity:	18 l
Noise level to DIN 45 635:	72 dB(A), without gas ballast
Mains connection:	3-ph, 400 V, 50 Hz / 460 V, 60 Hz
Installed motor rating at 50 Hz:	8 kW
Installed motor rating at 60 Hz:	9,2 kW
Electrical control:	Full Feature-Controller
Admissible ambient temperature:	+12 to +40°C
Dimensions (LxBxD):	1976 x 1130 x 1476 mm
Weight:	660 kg

Technical data are subject to change